



The universal clear application tape for maximum versatility and precision.

Clear Choice® is an ultra-clear application tape that provides exceptional performance and versatility for the widest range of sign applications.

AT60n Low Tack

Embossed film for transferring large cut graphics and protecting digital prints. Fine Texture for easy release/unwind and installation.

AT65 High Tack

Embossed film for transferring small and fine detail cut graphics and vinyl films with tight release liners. Fine Texture for easy release/unwind and installation.

AT75.1 High Tack

Embossed surface film ideal for small to medium size cut graphics with heavy texture air-egress micro channels for bubble-free lamination of tape to film.

New! Product Improvements

- Enhanced adhesion
- Improved release liner adhesion with Conform® characteristics
- Improvements to lifting and transferring graphics
- No adhesive residue with wet applications
- No water whitening upon contact with water/solution

Applications

Textured & Matte Finish Vinyl Films
Fine Lettering
Textured Wrap, Window, & Wall Films
Thermal Die Cuts

Product Information

Clear film
Repositionable
Easy handling and removal
No milky residue and water whitening when used for wet applications

AT75.1 vs AT60n ▼ See the difference!



TECHNICAL DATA ▶

Physical Properties		AT60n	AT65	AT75.1
Color	Transparent	Adhesive Acrylic	Acrylic	Modified polyacrylate
Shelf Life	1 Year	Caliper Embossed Polypropylene 3.7 mil (93 μ)	Embossed Polypropylene 3.7 mil (93.7 μ)	Embossed MDPE 4.25 mil (106.4 μ)
		Tack Level Low	High	High
		Adhesion to Steel* 1-4 N/100 mm (1-3 oz.)	2.1-6.5 N/100 mm (2 - 6 oz.)	2.1 N/25 mm (7.5 oz.)
		Die-Cut Graphics Size Large	Small-Med	Small-Med
		Wet Application Installation Good	Excellent	Excellent
		Compatible Vinyl Gloss/Smooth	Gloss/Smooth	Gloss/Smooth and Matte/Textured Vinyl
		Tensile 25 MPa (3600 psi)	25 MPa (3600 psi)	13 MPa (2000 psi)
		Elongation 750%	750%	300-500%

* TEST METHOD: PSTC-101



WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.